

SEYİR

VIDEO RECORDING SOLUTIONS

SMART CAMERA SYSTEMS



Video Recorder



DSM Camera



Eyeball Mobile Camera



Eyeball Outdoor Mobile Camera



SD Card



HIGH PERFORMANCE MAXIMUM SAFETY

Your vehicles are much safer with smart camera systems that can be easily integrated into all your vehicle groups, including tow trucks, buses, school buses and taxis.

Seyir Mobil Smart Camera Solution, which records the operating hours of your vehicles, offers the opportunity to monitor all events that may occur during the journey. The system, which analyzes driver behaviors such as yawning, fatigue, seat belt use, phone use and smoking with the optional DSM and in-car imaging and recording with high recording capacity, offers maximum security in your operational activities.

Depending on your preference, the system offers "Online" options that allow instant remote viewing or "Offline" options that only record on the device.

SMART CAMERA SYSTEMS

TECHNICAL SPECIFICATIONS

Video Recorder (DashCam) CDR8213-GFW

Power Source	9 V-16 V DC
Power Consumption	≤ 12W
Image sensor	1/2.8" CMOS
Max. Resolution	1920 (Y) × 1080 (D)
Diaphragm	F1,7
Field of view	Y: 128,6° Y: 69.4° D: 153.4°
Main Stream	CH1: 1080P/720P/960H/D1/CIF CH2-CH4: 720P/960H/D1/CIF
Video Compression Type	H.264/H.265
Frame Rate	25/30 fps
Built-in Microphone	Speaker (optional) Two-way audio support (optional)
Connection	Built-in GPS and 4G
Memory	Support dual TF cards up to 256GB each
Additional Camera	2 pieces
Durability	IP52

Eyeball Mobile Camera HAC-HMW3200L-0210B-S5

Power Source	12V ±%30 DC
Power Consumption	Maks 1,9 W (12 V DC, IR açık)
Image Sensor	1/2,7" CMOS
Max. Resolution	1920 (Y) × 1080 (D)
Diaphragm	F2,0
Focal Length	2.0 mm
Field of view	Y: 132 ° D: 69 ° D: 164 °
Min. Illumination	0,02 Lux/F2,0 30IRE, 0 Lux IR açık
Illumination Distance	3 m
Built-in Microphone	Var
Frame Rate	1280 × 720 @ 50/60fps 1920 × 1080 @ 25/30 fps
Durability	Darbeye dayanıklı



Effective logistics provides planning.



With the measures to be taken financial losses gets ahead of it.



DSM Camera CDM5110-CYP

Power Source	9 V-16 V DC
Power Consumption	< 2.5 W
Image sensor	1/4" CMOS
Max. Resolution	1280 (Y) × 720 (D)
Diaphragm	F1,7
Field of view	Y: 61,8° D: 37,5°
Frame Rate	50 Hz: 1280 × 720@25 fps 60 Hz: 1280 × 720@30 fps
Illumination Distance	3m
Minimum Illumination	0,1 lux
Built-in Microphone	Not available
Durability	IP52

Eyeball Outdoor Mobile Camera HAC-HDW3200G-M

Power Source	12V ±30% DC
Power Consumption	Max 2.3W (12V DC, IR açık)
Görüntü sensörü	1/2.7" CMOS
Image Sensor	1920 (Y) × 1080 (D)
Diaphragm	F2,0
Field of view	Y: 101° D: 54°
Frame Rate	1280 × 720 @ 50/60fps 1920 × 1080 @ 25/30 fps
Illumination Distance	20m
Minimum Illumination	0,2 lux
Built-in Microphone	Available
Durability	IP67

SD Cart TF-P100/256GB

Capacity	256 gb
Reading Speed	up to 100MB/s
Write Speed	up to 40MB/s
Speed Rating	C10/U3/V30
File System	exFAT
Protection Levels	High and low temperature resistant, Waterproof, anti-magnetic Anti X-ray



High and safe Provides registration.



In different vehicle types available.